



RAW TRAVERTINE

Textured and conformable self adhesive vinyl covering for walls and furniture

Warranty
10 YEARS

Application temperature
FROM +15°C TO +25°C

Storage from +5°C to +35°C
3 YEARS

LENGTH ↔ **50 m**

WIDTH ↔ **122 cm**



CHARACTERISTICS

Primer/Primer +	✓
Kraft paper release liner	✓
Stretchable	✓
Calendered polymeric	✓
Interior installation	✓
Outside installation	✗
UV-Resistant	✓
Permanent Air Release	✓
Adhesive	
Appearance	Mat
Thickness	240 μ
Scratch-proof	Average

CERTIFICATIONS

CE	✓
IMO	✓
MED	✓
RAIL	✓
REACH	✓
TCHIBO	✓
TABER TEST	✓
VOC	✓

GENERAL

ADHESIVE STRENGTH :

91 minutes after installation 1.04 Kg/cm
24 hours after installation: 1.43 Kg/cm
3 days after installation: 1.51 Kg/cm
7 days after installation: 1.65kg/cm

ADHESIVE STRENGTH AT HIGH TEMPERATURE :

After the 1st day: 1.37 Kg/cm
After 7 days: 1.03 Kg/cm

DURABILITY :

This product offers exceptional resistance to water, dirt, abrasion, UV rays and wear (yellowing, crackling, scaling, delamination).

MAINTENANCE :

For daily care and maintenance of the film use only neutral pH detergents, do not use products with too much acidic or basic pH.
- Hot water (not boiling) can help eliminate stubborn stains
- In some cases, even a solution based on isopropyl alcohol and water can be effective (70% ISO 30% H2O. Not on printed Cover Styl)
- Use only soft cloths or sponges to clean the vinyl (except glitter)
- If persistent stains are present it means that care and maintenance have not been performed correctly. In this case carry out a repair with patch (not guaranteed but effective and economical) or complete replacement of the vinyl;
- Don't use any organic-based cleaning product like ammonia or polish to clean vinyl